

Weatherproofing Tape

- Mastic and adhesive tape optionsCombined kits available

Adhesive Tape Options				
	Model Number	Thickness	Width	Length
	AWPT-A51W006-F	0.19 ± 0.01 mm	50.8 ± 0.5 mm	6000 ± 50 mm

Mastic Tape Options				
	Model Number	Thickness	Width	Length
	AWPT-M63W06M-F	2.5 ± 0.25 mm	63 ± 2.5 mm	600 ± 50 mm

Weatherproofing Tape Kit Options						
	Model Number	Included Products	Quantity	Thickness	Width	Length
	AWPTK-001	Adhesive	1 each	0.19 ± 0.01 mm	50.8 ± 0.5 mm	6.0 ± 0.05 m
		Adhesive	2 each	0.19 ± 0.01 mm	19 ± 0.5 mm	20 ± 0.05 m
		Mastic	6 each	2.5 ± 0.25 mm	63 ± 2.5 mm	600 ± 50 mm

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.



Weatherproofing Tape

Adhesive Tape Chai	racteristics			
Tensile Strength		≥ 3.5 kNm		
Elongation at Break		≥ 200%		
Breakdown Voltage		≥ 8 kV		
Adhesive Power		≥ 0.18 kV/m		
UV Resistance, minimum with no degradation		≥ 1,000 hours		
Weather Resistance Test Method		04AS00-03.6.0 / MIL-STD-1344A, Method 1002		
RoHS Compliant		Yes		
Mastic Tape Charac	teristics			
Heat Resistance		85° C (185° F) / 24 hour - No Liquid		
Elasticity	-17.8° C (0° F)	> 160%		
	25° C (77° F)	> 170%		
UV resistance, minimumwith no degradation		Butyl test method in QUV weatherometer cycle of 8 hours UV at 65.6° C (150° F) then 4 hours of condensation 40° C (104° F) / PVC tape test method UL 510, ASTM D1000		
RoHS Compliant		Yes		

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.