

S-2-CPUSE-H-N

Two-way Reactive Power Splitter, 698–2700 MHz



OBSOLETE

This product was discontinued on: July 31, 2014

Replaced By:

S-2-CPUSE-H-NI6	Two-way Reactive Power Splitter, 555–2700 MHz
S-2-CPUSE-H-NI6X	Two-way Reactive Power Splitter, 578–2700 MHz

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Power splitter

General Specifications

Device Type	Splitter
Application	Indoor/Outdoor
Color	Black
Inner Contact Plating	Silver
Interface	N Female
Outer Contact Plating	Trimetal

Dimensions

Height	25 mm 0.984 in
Width	61 mm 2.402 in
Length	211 mm 8.307 in

Electrical Specifications

3rd Order IMD	-150 dBc
3rd Order IMD Test Method	Two +43 dBm carriers

S-2-CPUSE-H-N

Return Loss, minimum	20.8 dB
Average Power, maximum	300 W
Dissipative Loss at Frequency Band	0.1 dB @ 698–2700 MHz
Impedance	50 ohm
Operating Frequency Band	698 – 2700 MHz
Peak Power, maximum	3 kW
Power Rating, Splitting	300 W
Reflected Power, maximum	300 W
Split Loss	3 dB
VSWR	1.2

Environmental Specifications

Operating Temperature	-25 °C to +85 °C (-13 °F to +185 °F)
Relative Humidity	Up to 100%
Ingress Protection Test Method	IEC 60529:2001, IP65

Packaging and Weights

Height, packed	43 mm 1.693 in
Width, packed	76 mm 2.992 in
Length, packed	258 mm 10.157 in
Volume	833300 mm ³ 50.851 in ³
Weight, gross	0.41 kg 0.904 lb
Weight, net	0.34 kg 0.75 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

